



WUNDERPLUG PIPE PLUG

WBP2

STANDARD BY-PASS

INFLATION
2.5
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WBP2** range of pipeplugs is designed for standard pipe plugging operations and offers a very wide operating range, from 35 to 4200 mm, while maintaining reduced weight and compact length.

The bypass allows fluids to pass through or to carry out tests. The maximum back pressure, depending on the operating diameter, is up to 2 bar.

The inflation pressure is tested up to three times the indicated pressure, ensuring safety and durability.

The **WUNDERPLUG WBP2** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE MM	Ø INSERTION MM	LENGTH MM	By • PASS "	WEIGHT KG	BACK PRESSURE Bar	Air Needed L	INFLATING PRESSURE bar
WBP2 - 3570	35 • 70	32	200	M6	0,4	1	•	•
WBP2 - 50100	50 • 100	45	280	1/4 "	0,9	1	•	•
WBP2 - 70150	70 • 150	65	320	1/2 "	1,4	1	•	•
WBP2 - 100200	100 • 200	85	500	1 "	2,1	1	•	•
WBP2 - 150300	150 • 300	135	500	2 "	7,2	1	•	•
WBP2 - 200400	200 • 400	182	600	2 "	8,3	1	•	•
WBP2 - 200500	200 • 500	182	750	2 "	9,6	1	•	•
WBP2 - 300600	300 • 600	280	800	2 "	19	1	•	•
WBP2 375750	375 • 750	355	1000	2 "	32	1	•	•
WBP2 400800	400 • 800	355	1000	2 "	32	1	•	•
WBP2 - 500800	500 • 800	480	1050	2 "	38	1	•	•
WBP2 - 5001000	500 • 1000	480	1050	2 "	38	1	•	•
WBP2 - 5001200	500 • 1200	480	1400	2 "	50	1	•	•
WBP2 - 5001400	500 • 1400	480	1900	2 "	70	1	•	•
WBP2 - 6001200	600 • 1200	580	1250	2 "	65	1	•	•
WBP2 - 6001600	600 • 1600	580	1900	2 "	99	1	•	•
WBP2 - 8001200	800 • 1200	780	1600	2 "	112	1	•	•
WBP2 - 8001600	800 • 1600	780	2000	2 "	140	1	•	•
WBP2 - 8002000	800 • 2000	780	2400	2 "	183	1	•	•
WBP2 - 8002200	800 • 2200	780	3200	2 "	244	1	•	•
WBP2 - 12002400	1200 • 2400	1180	3000	2 "	350	1	•	•
WBP2 - 12002800	1200 • 2800	1180	3000	2 "	500	1	•	•
WBP2 - 18003600	1800 • 3600	1780	4000	2 "	630	1	•	•
WBP2 - 18004200	1800 • 4200	1780	6000	2 "	945	1	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING