



WUNDERPLUG PIPE PLUG

WC & WCBP SIMPLE & BY-PASS

INFLATION
3
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7,5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WC & WCBP** range of pipeplugs is designed for pipe plugging operations where the available installation length is limited. The operating range is more limited than the WS2 and WBP2 ranges.

The maximum back pressure, depending on the operating diameter, is up to 1.5 bar.

The inflation pressure is tested up to three times the indicated pressure, ensuring safety and durability.

The **WUNDERPLUG WC & WCBP** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE MM	Ø INSERTION MM	LENGTH MM	BY • PASS	WEIGHT KG	BACK PRESSURE Bar	Air Needed L	INFLATING PRESSURE bar
WC-50100	50 • 100	45	150	•	0,3	0,5	•	•
WC-70150	70 • 150	65	200	•	0,4	0,5	•	•
WC-100200	100 • 200	85	200	•	1	0,5	•	•
WC-150300	150 • 300	135	300	•	2	0,5	•	•
WC-200400	200 • 400	182	400	•	3	0,5	•	•
WC-300600	300 • 600	280	600	•	6	0,5	•	•

	OPERATING RANGE MM	Ø INSERTION MM	LENGTH MM	BY • PASS	WEIGHT KG	BACK PRESSURE Bar	Air Needed L	INFLATING PRESSURE bar
WCBP-50100	50 • 100	45	150	1/4 "	0,7	0,5	•	•
WCBP-70150	70 • 150	65	200	1/4 "	1,2	0,5	•	•
WCBP-100200	100 • 200	85	200	1/2 "	1,7	0,5	•	•
WCBP-150300	150 • 300	135	300	1 "	4,5	0,5	•	•
WCBP-200400	200 • 400	182	400	1 "	6,5	0,5	•	•
WCBP-300600	300 • 600	280	600	2 "	14	0,5	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING