



WUNDERPLUG PIPE PLUG

WCONHP

CONICAL HIGH PRESSURE

INFLATION UP TO
2.0
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WCONHP** range of pipeplugs is designed for pipe plugging operations in difficult-to-access locations, thanks to its flexible structure, and offers a wide operating range from 100 to 3600 mm.

The maximum back pressure, depending on the operating diameter, is up to 1 bar.

The inflation pressure is tested up to three times the indicated pressure, ensuring safety and durability.

The **WUNDERPLUG WCONHP** pipeplug range is also available on request in NITRILE, EPDM and CHLORO-PRENE rubber.

	OPERATING RANGE mm	Ø INSERTION mm	LENGTH mm	WEIGHT kg	BY-PASS pouce	BACK PRESSURE bar	TIGHTENING TORQUE N/M	INFLATING PRESSURE bar
WCONHP-100200	100 • 200	90	550	1,5	•	1	•	•
WCONHP-150400	150 • 400	130	740	2,5	•	1	•	•
WCONHP-250600	250 • 600	220	1000	5,5	•	1	•	•
WCONHP-300800	300 • 800	260	1320	17	•	1	•	•
WCONHP-4001000	400 • 1000	350	1640	29	•	1	•	•
WCONHP-5001200	500 • 1200	400	1880	40	•	1	•	•
WCONHP-5001400	500 • 1400	430	2330	48	•	1	•	•
WCONHP-5001500	500 • 1500	470	2590	70	•	1	•	•
WCONHP-6001600	600 • 1600	500	2640	75	•	1	•	•
WCONHP-8001800	800 • 1800	600	2890	120	•	1	•	•
WCONHP-10002200	1000 • 2200	800	3340	180	•	0,5	•	•
WCONHP-15002800	1500 • 2800	1000	3800	260	•	0,4	•	•
WCONHP-22003600	2200 • 3600	1200	4460	400	•	0,4	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING