



WUNDERPLUG PIPE PLUG

WCONHPBP

CONICAL HIGH PRESSURE BY-PASS

INFLATION
2.0
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



Special Layers Provide Extra Sealing

The **WUNDERPLUG WCONHPBP** range of pipeplugs is designed for pipe plugging operations in difficult-to-access locations, thanks to its flexible structure, and offers a wide operating range from 100 to 3600 mm.

The bypass allows fluids to pass through or to carry out tests.

The maximum back pressure, depending on the operating diameter, is up to 1 bar.

The inflation pressure is tested up to three times the indicated pressure, ensuring safety and durability.

The **WUNDERPLUG WCONHPBP** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE mm	Ø INSERTION mm	LENGTH mm	WEIGHT kg	BY-PASS pouces	BACK PRESSURE bar	TIGHTENING TORQUE N/m	INFLATING PRESSURE bar
WCONHPBP-250600	260 • 600	220	1000	15,5	1 "	1	•	•
WCONHPBP-300800	300 • 800	260	1320	27	2 "	1	•	•
WCONHPBP-4001000	400 • 1000	350	1640	39	2 "	1	•	•
WCONHPBP-5001200	500 • 1200	400	1880	50	2 "	1	•	•
WCONHPBP-5001400	500 • 1400	430	2330	58	2 "	1	•	•
WCONHPBP-5001500	500 • 1500	470	2590	80	2 "	1	•	•
WCONHPBP-6001600	600 • 1600	500	2640	95	2 "	1	•	•
WCONHPBP-8001800	800 • 1800	600	2890	140	2 "	1	•	•
WCONHPBP-10002200	1000 • 2200	800	3340	200	2 "	0,5	•	•
WCONHPBP-15002800	1500 • 2800	1000	3800	280	2 "	0,4	•	•
WCONHPBP-22003600	2200 • 3600	1200	4460	420	2 "	0,4	•	•



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

FACTORY AGENT



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING