



WUNDERPLUG PIPE PLUG

WCS CUSHION BY-PASS

INFLATION
1.0
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WCS** range of pipeplugs is designed for pipe plugging operations where the access point is smaller than the pipe diameter to be sealed. Thanks to their flexible structure, the plugs can be folded to pass through narrow manholes or restricted access points, making them ideal when large pipe diameters must be sealed but the installation opening is limited.

They offer a wide operating range from 200 to 2400 mm.

The bypass allows fluids to pass through or to carry out tests.

The inflation pressure is tested up to three times the indicated pressure, ensuring safety and durability.

The **WUNDERPLUG WCS** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE mm	Ø INSERTION mm	LENGTH mm	WEIGHT kg	BYPASS poises	BACK PRESSURE bar	TIGHTENING TORQUE N/M
WCS-200400	200 • 200	•	210	12	1/4"	•	•
WCS-300600	300 • 600	•	400	12,2	1/4"	•	•
WCS-375600	375 • 600	•	460	22	1/4"	•	•
WCS-600900	600 • 900	•	920	36	1/4"	•	•
WCS-6001000	600 • 1000	•	1225	40	1/4"	•	•
WCS-8001200	800 • 1200	•	1500	61	1/4"	•	•
WCS-10001400	1000 • 1400	•	1650	65	1/4"	•	•
WCS-12001600	1200 • 1600	•	1900	85	1/4"	•	•
WCS-14001800	1400 • 1800	•	1900	95	1/4"	•	•
WCON-8001800	1500 • 2000	•	1900	119	1/4"	•	•
WCS-18002200	1800 • 2200	•	1900	144	1/4"	•	•
WCS-22002400	2200 • 2400	•	2400	172	1/4"	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING