



WUNDERPLUG PIPE PLUG

WEF

LARGE BYPASS

INFLATION
1.5
BAR

COMPOSITION

NR SBR RUBBER – KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm – 2 stainless steel hooks.



The **WUNDERPLUG WEF** range of pipeplugs is designed for pipe plugging operations requiring a large bypass, offering a very wide operating range, from 100 to 1200 mm.

The bypass allows fluids to pass through or to carry out tests.

The inflation pressure is tested up to three times the indicated pressure, ensuring safety and durability.

The **WUNDERPLUG WEF** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE MM	Ø INSERTION MM	LENGTH MM	By • PASS "	WEIGHT KG	BACK PRESSURE Bar	Air Needed L	INFLATING PRESSURE bar
WEF • 100200	100 • 200	92	400	2 "	2,5	0,5	•	•
WEF • 150300	150 • 300	140	520	4 "	5,8	0,5	•	•
WEF • 200500	200 • 500	185	680	4 "	12,1	0,5	•	•
WEF • 300600	300 • 600	280	680	4 "	18	0,5	•	•
WEF • 300750	300 • 750	280	750	4 "	25	0,5	•	•
WEF • 500800	500 • 800	440	680	6 "	38	0,5	•	•
WEF • 5001200	500 • 1200	440	980	8 "	47	0,5	•	•



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

FACTORY AGENT



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING