



INFLATION
12
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

FACTORY AGENT



www.ezeseal.com
contact@ezeseal.com

The **WUNDERPLUG WLHB** Heavy Lifting Bags are designed for lifting heavy loads, up to 108 T, with a maximum lifting height of 59 cm, during natural disasters, accident recovery operations or heavy load installation.

Unlike standard lifting bags, the **WLHB** system features a modular design. The lifting discs can be combined and stacked together using an interlocking system, allowing greater lifting capacity and adaptability depending on operational requirements.

	DIAMETER mm	THICKNESS mm	Max lifting capacity at max contact	Max lifting with full load plate contact	End lifting capacity	WEIGHT kg	Air Needed L	INFLATING PRESSURE bar
WLHB-565	565	90	30	14	7	18,5	442	12
WLHB-890	890	90	75	41	12	34,5	1470	12
WLHB-1350	1350	115	171	108	15	58	5050	12



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING