



WUNDERPLUG PIPE PLUG

WHP HIGH PRESSURE

INFLATION
6/12
BAR

COMPOSITION
NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WHP** range of pipeplugs is designed for pipe plugging operations at higher back pressures than the standard range. The maximum back pressure, depending on the operating diameter, is up to 6 bar. They are equipped with a 7.5 mm European-type brass quick coupling and retaining hooks. The inflation pressure is tested up to three times the indicated pressure, ensuring safety and durability.

The **WUNDERPLUG WHP** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE mm	Ø INSERTION mm	LENGTH mm	WEIGHT kg	BY-PASS poices	BACK PRESSURE bar	TIGHTENING TORQUE N/M	INFLATING PRESSURE bar
WHP6-3550	35 • 50	32	200	0,2	•	3	•	•
WHP12-50	50 • 50	45	280	0,4	•	6	•	•
WHP6-5070	50 • 70	45	280	0,4	•	3	•	•
WHP12-70	50 • 70	65	320	0,6	•	6	•	•
WHP6-70100	70 • 70	65	320	0,6	•	3	•	•
WHP12-100	70 • 100	85	500	1	•	6	•	•
WHP6-100150	100 • 100	85	500	1	•	3	•	•
WHP12-150	100 • 150	135	500	2,2	•	6	•	•
WHP6-150200	150 • 200	135	500	2,2	•	3	•	•
WHP12-200	200 • 200	182	600	3,4	•	6	•	•
WHP6-200300	200 • 300	182	600	3,4	•	3	•	•
WHP12-300	300 • 300	280	800	8,1	•	6	•	•
WHP6-300400	300 • 400	280	800	8,1	•	3	•	•
WHP12-375	375 • 375	355	1000	13,7	•	6	•	•
WHP6-375500	375 • 500	355	1000	13,7	•	3	•	•
WHP12-500	500 • 500	480	1050	24,9	•	6	•	•
WHP6-500600	500 • 600	480	1050	24,9	•	3	•	•
WHP12-600	600 • 600	580	1250	36,3	•	6	•	•
WHP6-600700	600 • 700	580	1250	36,3	•	3	•	•
WHP12-800	800 • 800	780	1200	55	•	6	•	•
WHP6-8001000	800 • 1000	780	1200	55	•	3	•	•
WHP12-1200	1200 • 1200	1180	1600	115	•	6	•	•
WHP6-12001400	1200 • 1400	1180	1600	115	•	3	•	•
WHP12-1800	1800 • 1800	1780	2000	180	•	6	•	•
WHP6-18002000	1800 • 2000	1780	2000	180	•	3	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING