



INFLATION
8/12
BAR

COMPOSITION
NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7,5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

FACTORY AGENT



www.ezeseal.com
contact@ezeseal.com

The **WUNDERPLUG WLB8** and **WLB12** lifting bags are designed for lifting heavy loads, up to 115 T, during natural disasters, accidents or heavy load installation operations.

They also allow the installation and maintenance of pipes.

They are approved for mining operations.

	DIMENSIONS CM	MAX LOAD T	LENGTH mm	WEIGHT KG	MAX HEIGHT CM	AIR NEEDED L	TIGHTENING TORQUE N/M	INFLATING PRESSURE bar
WLB-115	14x14x23	1,5	•	0,4	7,5	2,9	•	8
WLB-350	20x26x23	3,5	•	1	10	15,5	•	8
WLB-620	30x30x23	6,2	•	2	17	40	•	8
WLB-1030	38x38x23	10,3	•	3,8	21	85	•	8
WLB-1300	30x60x25	13	•	4	17	115	•	8
WLB-1840	50x50x25	18,4	•	6,4	29	198	•	8
WLB-2430	100x33x25	24,3	•	9,1	20	215	•	8
WLB-2700	60x60x25	27	•	9,8	36	380	•	8
WLB-3700	70x70x25	37	•	13,5	42	630	•	8
WLB-4870	80x80x25	48,7	•	17,8	47	945	•	8
WLB-6200	90x90x25	62	•	21	50	1450	•	8
WLB-7600	100x100x25	76,8	•	24,5	59	1580	•	8

	DIMENSIONS CM	MAX LOAD T	LENGTH mm	WEIGHT KG	MAX HEIGHT CM	AIR NEEDED L	TIGHTENING TORQUE N/M	INFLATING PRESSURE bar
WLB-170	14x14x23	1,7	•	0,4	7,5	2,9	•	12
WLB-520	20x26x23	5,2	•	1	10	15,5	•	12
WLB-940	30x30x23	9,4	•	2	17	40	•	12
WLB-1550	38x38x23	15,4	•	3,8	21	85	•	12
WLB-1940	30x60x25	19,4	•	4	17	115	•	12
WLB-2760	50x50x25	27,6	•	6,4	29	198	•	12
WLB-3640	100x33x25	36,4	•	9,1	20	215	•	12
WLB-4030	60x60x25	40,3	•	9,8	36	380	•	12
WLB-5540	70x70x25	55,4	•	13,5	42	630	•	12
WLB-7300	80x80x25	73	•	17,8	47	945	•	12
WLB-9300	90x90x25	93	•	21	50	1450	•	12
WLB-1150	100x100x25	115	•	24,5	59	1580	•	12



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING