



WUNDERPLUG PIPE PLUG

WS2 STANDARD

INFLATION
2.5
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WS2 range of pipeplugs** is designed for standard pipe plugging operations and offers a very wide operating range, from **35 to 4200 mm**, while maintaining **reduced weight and compact length**.

The **maximum back pressure**, depending on the operating diameter, is **up to 2 bar**.

The **inflation pressure** is tested up to **three times the indicated pressure**, ensuring **safety and durability**.

The **WUNDERPLUG WS2 pipeplug range** is also available on request in **NITRILE, EPDM and CHLOROPRENE rubber**.

	OPERATING RANGE MM	Ø INSERTION MM	LENGTH MM	BY • PASS	WEIGHT KG	BACK PRESSURE Bar	Air Needed L	INFLATING PRESSURE bar
WS2 • 3570	35 • 70	32	200	•	0,2	1	•	•
WS2 • 50100	50 • 100	45	280	•	0,4	1	•	•
WS2 • 70150	70 • 150	65	320	•	0,6	1	•	•
WS2 • 100200	100 • 200	85	500	•	1	1	•	•
WS2 • 150300	150 • 300	135	500	•	2,2	1	•	•
WS2 • 200400	200 • 400	182	600	•	3,4	1	•	•
WS2 • 200500	200 • 500	182	750	•	4,2	1	•	•
WS2 • 300600	300 • 600	280	800	•	8,1	1	•	•
WS2 • 375750	375 • 750	355	1000	•	13,7	1	•	•
WS2 • 400800	400 • 800	355	1000	•	13,7	1	•	•
WS2 • 500800	500 • 800	480	1050	•	24,9	1	•	•
WS2 • 5001000	500 • 1000	480	1050	•	24,9	1	•	•
WS2 • 5001200	500 • 1200	480	1400	•	33,2	1	•	•
WS2 • 5001400	500 • 1400	480	1900	•	52,5	1	•	•
WS2 • 6001200	600 • 1200	580	1250	•	36,3	1	•	•
WS2 • 6001600	600 • 1600	580	1900	•	48,5	1	•	•
WS2 • 8001200	800 • 1200	780	1600	•	55	1	•	•
WS2 • 8001600	800 • 1600	780	2000	•	69	1	•	•
WS2 • 8002000	800 • 2000	780	2400	•	98	1	•	•
WS2 • 8002200	800 • 2200	780	3200	•	129	1	•	•
WS2 • 12002400	1200 • 2400	1180	3000	•	190	1	•	•
WS2 • 12002800	1200 • 2800	1180	3000	•	248	1	•	•
WS2 • 18003600	1800 • 3600	1780	4000	•	330	1	•	•
WS2 • 18004200	1800 • 4200	1780	6000	•	500	1	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING