



WUNDERPLUG PIPE PLUG

WXC EXTRA SHORT

INFLATION
2.5
BAR

COMPOSITION
NR SBR RUBBER – KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm – 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WXC** range of pipeplugs is designed for branch connections, pipe connections and small-diameter pipes. They offer a wide operating range (from 20 to 2000 mm) while maintaining reduced weight and compact length.

The maximum back pressure, at the end of the operating range, is up to 1 bar and is tested at three times the service pressure, ensuring safety and durability.

They are equipped with a 7.5 mm European-type brass quick coupling and stainless steel hooks.

The **WUNDERPLUG WXC** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE mm	Ø INSERTION mm	LENGTH mm	WEIGHT kg	BY-PASS pouces	BACK PRESSURE bar	TIGHTENING TORQUE N/M	INFLATING PRESSURE bar
WXC-20	20 • 20	18	100	0,1	•	1	•	•
WXC-25	25 • 25	23	100	0,12	•	1	•	•
WXC-30	30 • 30	28	100	0,15	•	1	•	•
WXC-40	40 • 40	38	100	0,15	•	1	•	•
WXC-50	50 • 50	45	100	0,25	•	1	•	•
WXC-60	60 • 60	58	100	0,35	•	1	•	•
WXC-75	75 • 75	68	100	0,45	•	1	•	•
WXC-100	100 • 100	85	150	0,6	•	1	•	•
WXC-150	150 • 150	135	150	1,1	•	1	•	•
WXC-200	200 • 200	182	250	1,6	•	1	•	•
WXC-250	250 • 250	182	300	2,2	•	1	•	•
WXC-300	300 • 300	280	300	3,5	•	1	•	•
WXC-400	400 • 400	380	400	7,5	•	1	•	•
WXC-500	500 • 500	480	450	10,5	•	1	•	•
WXC-600	600 • 600	580	450	15	•	1	•	•
WXC-800	800 • 800	780	1200	41	•	1	•	•
WXC-1200	1200 • 1200	1180	1500	78	•	1	•	•
WXC-1800	1800 • 1800	1780	100	118	•	1	•	•
WXC-2030	20 • 30	18	100	0,1	•	1	•	•
WXC-3040	30 • 40	28	100	0,12	•	1	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING



WUNDERPLUG PIPE PLUG

WXC EXTRA SHORT

INFLATION
2.5
BAR

COMPOSITION

NR SBR RUBBER — KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm — 2 stainless steel hooks.



WUNDERPLUG DESIGN & IMPORT PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

The **WUNDERPLUG WXC** range of pipeplugs is designed for branch connections, pipe connections and small-diameter pipes. They offer a wide operating range (from 20 to 2000 mm) while maintaining reduced weight and compact length.

The maximum back pressure, at the end of the operating range, is up to 1 bar and is tested at three times the service pressure, ensuring safety and durability.

They are equipped with a 7.5 mm European-type brass quick coupling and stainless steel hooks.

The **WUNDERPLUG WXC** pipeplug range is also available on request in NITRILE, EPDM and CHLOROPRENE rubber.

	OPERATING RANGE mm	Ø INSERTION mm	LENGTH mm	WEIGHT kg	BY-PASS poise	BACK PRESSURE bar	TIGHTENING TORQUE N/M	INFLATING PRESSURE bar
WXC-3050	30 • 50	28	100	0,15	•	1	•	•
WXC-4050	40 • 50	38	100	0,15	•	1	•	•
WXC-5075	50 • 75	45	100	0,25	•	1	•	•
WXC-70100	70 • 100	65	150	0,35	•	1	•	•
WXC-100150	100 • 150	85	150	0,45	•	1	•	•
WXC-150200	150 • 200	135	200	0,6	•	1	•	•
WXC-200250	200 • 250	182	250	1,1	•	1	•	•
WXC-250300	250 • 300	235	300	2,2	•	1	•	•
WXC-300350	300 • 350	280	300	3,5	•	1	•	•
WXC-400450	400 • 450	380	450	4,4	•	1	•	•
WXC-500550	500 • 550	480	450	5,5	•	1	•	•
WXC-600650	600 • 650	580	450	18	•	1	•	•
WXC-8001000	800 • 1000	780	1200	40	•	1	•	•
WXC-12001400	1200 • 1400	1180	1600	78	•	1	•	•
WXC-18002000	1800 • 2000	1780	1500	118	•	1	•	•



www.ezeseal.com
contact@ezeseal.com



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING