



INFLATION
2.5
BAR

COMPOSITION
NR SBR RUBBER – KEVLAR FIBER
- 40 to + 80 °C

European brass quick coupling 7.5 mm – 2 stainless steel hooks.



WUNDERPLUG
DESIGN & IMPORT
PIPE PLUGS

All pipeplugs are serialized, traceable and tested.
Certificates available upon request.

Engineering studies and custom manufacturing available.

FACTORY AGENT



www.ezeseal.com
contact@ezeseal.com

The **WUNDERPLUG WXCBP** range of pipeplugs is designed for branch connection plugging and testing operations, pipe connections and small-diameter pipes. They offer a wide operating range from 20 to 2000 mm.

The **maximum back pressure**, at the end of the operating range, is up to 1 bar and is tested at three times the service pressure, ensuring safety and durability.

They are equipped with a 7.5 mm European-type brass quick coupling (1) and stainless steel retaining hooks.

The **WUNDERPLUG WXCBP** pipeplug range is also available on request in NITRILE, EPDM and CHLORO-PRENE rubber.

	OPERATING RANGE mm	Ø INSERTION mm	LENGTH mm	WEIGHT kg	BY-PASS pouce	BACK PRESSURE bar	TIGHTENING TORQUE N/m	INFLATING PRESSURE bar
WXCBP-30	30 • 30	28	50	0,14	M8	1	•	•
WXCBP-40	40 • 40	38	60	0,15	M8	1	•	•
WXCBP-50	50 • 50	45	80	0,25	1/8 "	1	•	•
WXCBP-60	60 • 60	58	80	0,35	1/8 "	1	•	•
WXCBP-75	75 • 75	65	100	0,45	1/4 "	1	•	•
WXCBP-100	100 • 100	85	150	0,6	1/2 "	1	•	•
WXCBP-150	150 • 150	135	150	1,5	1 "	1	•	•
WXCBP-200	200 • 200	182	200	2	2 "	1	•	•
WXCBP-250	250 • 250	235	300	2,5	2 "	1	•	•
WXCBP-300	300 • 300	280	300	3,2	2 "	1	•	•
WXCBP-400	400 • 400	380	450	4,2	2 "	1	•	•
WXCBP-500	500 • 500	480	450	5,4	2 "	1	•	•
WXCBP-600	600 • 600	580	450	6,5	2 "	1	•	•
WXCBP-800	800 • 800	780	1200	55	2 "	1	•	•
WXCBP-1200	1200 • 1200	1180	1600	135	2 "	1	•	•
WXCBP-1800	1800 • 1800	1780	1500	220	2 "	1	•	•
WXCBP-3040	30 • 40	28	50	0,14	M8	1	•	•
WXCBP-5075	50 • 75	45	80	0,25	1/8 "	1	•	•
WXCBP-70100	70 • 100	65	150	0,45	1/4 "	1	•	•
WXCBP-100150	100 • 150	85	150	0,60	1/2 "	1	•	•
WXCBP-150200	150 • 200	135	200	1,5	1 "	1	•	•
WXCBP-200250	200 • 250	182	250	2	2 "	1	•	•
WXCBP-250300	250 • 300	235	300	2,5	2 "	1	•	•
WXCBP-300350	300 • 350	280	300	3,2	2 "	1	•	•
WXCBP-400450	400 • 450	380	450	4,2	2 "	1	•	•
WXCBP-500550	500 • 550	480	450	5,4	2 "	1	•	•
WXCBP-600650	600 • 650	580	450	6,5	2 "	1	•	•
WXCBP-8001000	800 • 1000	780	1200	55	2 "	1	•	•
WXCBP-12001400	1200 • 1400	1180	1600	135	2 "	1	•	•
WXCBP-18002000	1800 • 2000	1780	1500	220	2 "	1	•	•



INFLATION HOSE
5 & 10 M



SAFETY CABLE
5 & 10 M



SAFETY INFLATION
CONTROL UNIT



VALVE ADAPTER
AUTO / EUROPEAN



SAFETY QUICK
COUPLING